



SPECS

FRAME	
SIZES	M, L, XL
COLORS	Chameleon Saturn
FRAME	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
FORK	Fox 34 Float SC Performance Elite Live Valve, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
SHOCK	Fox Performance Elite Live Valve, 165/45, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR XC Flat, composite, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STEM	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SEATPOST	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm XL: 150mm travel / 30.9 x 445mm
SADDLE	Fi'zi:k Antares R5 with Kium rails
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore XT SL-M8100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore XT RD-M8100
BRAKES	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	Shimano Deore XT M8100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano Deore XT, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant XCR 1 29 Carbon WheelSystem
HUBS	Giant XCR 1 29 Carbon WheelSystem
SPOKES	Giant XCR 1 29 Carbon WheelSystem
TIRES	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	390	420	465	495
Seat Tube Angle	75,5°	75,5°	75,5°	75,5°
Top Tube Length (mm)	572	604	626	653
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67,5°	67,5°	67,5°	67,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Wheelbase (mm)	1127	1159	1183	1212
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	70	70	70
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.